

## RE STAGED ELECTRIC HEATER

---



- Air Volume: 400 - 22000 cfm
- Maximum SP: 3" wg. @ standard air density

The Modular Electric Heater is used for tempering make-up air for installations requiring frequent air changes. The units are rated up to 235KW and 22,000 CFMs, depending on heating requirements. The heaters are intended for indoor or outdoor installations in commercial kitchens, factories, foundries and similar commercial and industrial occupancies.

Combination packages that include both exhaust and supply fans mounted on a single roof curb are also available, please contact your sales representative for more information.

---

### FEATURES & BENEFITS

- UL Listed Insert - The electric insert is a UL Listed sub-assembly.
- Staged Heating Control.
- 120 volt control transformer.
- Galvanized, fully insulated casing.
- Temperature control system.
- Access doors on both sides of unit.
- Lifting points.
- Blower interlock.
- Airflow proving switch.
- Coil observation port.
- High temperature limit.
- Motor starter.
- Vibration isolation.
- High efficiency motors.
- Adjustable drive sheaves.
- Horizontal or down discharge.
- Disconnect switch.

---

### OPTIONS

- Motorized Intake Damper.
- Remote Control Panel.
- Freeze Stat with Bypass Timer.
- Room Temperature Control.
- Convenience Outlet.
- Mixing Box with Damper Control.
- DX Cooling Coils.
- Evaporative Cooler Intake.

- V-Bank Filter Intake.
- Sloped Filter Intake.
- Auxiliary Starters.
- Indoor Hanging Cradle.
- VAV Packages.
- Roof Curbs.
- Clogged Filter Switch
- Cooling Thermostat and Interlock
- Extra Set of V-Belts