



UNIT INFORMATION

MODEL	A	B	C	D	E	F	G	H	J	K	L	M	N	P	R	S	AA	AB	AC	AD	AA'	AB'	AD'	AA''	AB''	AD''
D.500-G18	234-1/2	54-3/8	56-3/8	51-1/8	51-1/4	51-5/8	9-1/2	114-7/16	35	84	133	199-5/8	241-7/8	6-5/16	22-3/8	49-1/2	18	4-1/2	5-3/4	20	19	16"x20"x2" (6)	88000 CFM = 762 FPM	88000 CFM = 762 FPM	88000 CFM = 762 FPM	88000 CFM = 762 FPM
D.750-G18	234-1/2	54-3/8	56-3/8	51-1/8	51-1/4	51-5/8	9-1/2	114-7/16	35	84	133	199-5/8	241-7/8	6-5/16	22-3/8	49-1/2	18	4-1/2	5-3/4	20	19	16"x20"x2" (6)	88000 CFM = 762 FPM	88000 CFM = 762 FPM	88000 CFM = 762 FPM	88000 CFM = 762 FPM
D.1000-G18	234-1/2	54-3/8	56-3/8	51-1/8	51-1/4	51-5/8	9-1/2	114-7/16	35	84	133	199-5/8	241-7/8	6-5/16	22-3/8	49-1/2	18	4-1/2	5-3/4	20	19	16"x20"x2" (6)	88000 CFM = 762 FPM	88000 CFM = 762 FPM	88000 CFM = 762 FPM	88000 CFM = 762 FPM
D.1500-G18	234-1/2	54-3/8	56-3/8	51-1/8	51-1/4	51-5/8	9-1/2	114-7/16	35	84	133	199-5/8	241-7/8	6-5/16	22-3/8	49-1/2	18	4-1/2	5-3/4	20	19	16"x20"x2" (6)	88000 CFM = 762 FPM	88000 CFM = 762 FPM	88000 CFM = 762 FPM	88000 CFM = 762 FPM
D.2000-G18	292-7/8	60-7/16	64-3/8	59-1/8	59-1/4	59-1/4	13-9/16	151	42	115-3/16	171-3/16	255-7/8	310-3/16	5-1/4	31-1/2	56-19/16	23-1/2	4-1/2	5-3/4	23-1/2	17-1/2	16"x20"x2" (10)	81300 CFM = 743 FPM	81300 CFM = 743 FPM	81300 CFM = 743 FPM	81300 CFM = 743 FPM
D.2500-G18	292-7/8	60-7/16	64-3/8	59-1/8	59-1/4	59-1/4	13-9/16	151	42	115-3/16	171-3/16	255-7/8	310-3/16	5-1/4	31-1/2	56-19/16	23-1/2	4-1/2	5-3/4	23-1/2	17-1/2	16"x20"x2" (10)	81300 CFM = 743 FPM	81300 CFM = 743 FPM	81300 CFM = 743 FPM	81300 CFM = 743 FPM
D.3000-G18	292-7/8	60-7/16	64-3/8	59-1/8	59-1/4	59-1/4	13-9/16	151	42	115-3/16	171-3/16	255-7/8	310-3/16	5-1/4	31-1/2	56-19/16	23-1/2	4-1/2	5-3/4	23-1/2	17-1/2	16"x20"x2" (10)	81300 CFM = 743 FPM	81300 CFM = 743 FPM	81300 CFM = 743 FPM	81300 CFM = 743 FPM

UNIT INFORMATION

MODEL	BURNER BTU RANGE (QMBH)	GAS PRESSURE (MIN. MAX.)	GAS CONNECTION (T" (KQBT))	TONNAGE RANGE (MIN. MAX.)	TOT. WEIGHT (LBS)	WATER SIZE & QTY (VEL. & MAX. CFM/INCHES)	MAX. FLOW RATE (GPH)
D.500-G18	12"	18	3/50	7" WC 14" WC	15 TON 15 TON	1863 LBS 20"x25"x2" (8)	348 FPM 14
D.750-G18	18"	27.5	8/25	7" WC 14" WC	15 TON 15 TON	1870 LBS 20"x25"x2" (8)	348 FPM 14
D.1000-G18	24"	36.6	11/00	7" WC 14" WC	15 TON 15 TON	1875 LBS 20"x25"x2" (8)	348 FPM 14
D.1500-G18	24"	36.6	11/00	7" WC 14" WC	15 TON 15 TON	1895 LBS 20"x25"x2" (8)	348 FPM 14
D.2000-G18	30"	45.8	13/75	7" WC 5 PSI 1-1/4"	15 TON 15 TON	2950 LBS 16"x20"x2" (15)	572 FPM 24
D.2500-G18	30"	45.8	13/75	7" WC 5 PSI 1-1/4"	15 TON 15 TON	2965 LBS 16"x20"x2" (15)	572 FPM 24

CONDENSER INFORMATION

MODEL	WEIGHT#	#1	#2	#3	CC	DD	EE
15 TON-G18/S91	LBS	5	TON	5	TON	32-13/16	76-3/16
15 TON-G18/S91	LBS	5	TON	5	TON	32-13/16	76-3/16
15 TON-G18/S91	LBS	5	TON	5	TON	32-13/16	76-3/16
15 TON-G18/S91	LBS	5	TON	5	TON	32-13/16	76-3/16

UNIT INFORMATION

MODEL #	T	U	V
D.18	14-1/2	22	19
D.18	18-1/2	27-1/4	21
D.18	21-1/2	30-1/4	21
D.18	23	33-3/4	24-3/4
D.18	23-1/2	39-3/8	28
D.18	29-1/2	38-7/8	38
D.18	30-5/8	43-3/8	33
D.18	33-1/2	52-3/4	40

EXHAUST UNIT DIMENSIONS

MODEL #	T	U	V
D.18	14-1/2	22	19
D.18	18-1/2	27-1/4	21
D.18	21-1/2	30-1/4	21
D.18	23	33-3/4	24-3/4
D.18	23-1/2	39-3/8	28
D.18	29-1/2	38-7/8	38
D.18	30-5/8	43-3/8	33
D.18	33-1/2	52-3/4	40

*** 9 INCH HIGH EXHAUST ADAPTER MAY BE REQUIRED ***

20 INCH HIGH EQUIPMENT CURB

MAX. ROOF OPENING 2" SMALLER THAN CURB OPENING DIMENSION

STANDARD EVAPORATIVE COOLING UNIT

CELD EX EVAPORATIVE COOLING UNIT

DISCHARGE OPENING

CURB OUTER WALL

48 IN CLEARANCE REQUIRED ABOVE CONDENSERS

CONDENSER 1

CONDENSER 2

CONDENSER 3

COIL ACCESS DOOR

SERVICE DISCONNECT SWITCH BLOWER/MOTOR ACCESS DOOR

DIRECT FIRED CONDENSER MODULE

CONDENSER SUPPLEMENT MODULE

FILTER ACCESS DOOR

SLOPED FILTER INTAKE

WATER DRAIN WATER INLET (BELOW) **

AIRFLOW

DISCHARGE OPENING

COOLING COIL MODULE

CURB OUTER WALL

CONDENSER 1

CONDENSER 2

CONDENSER 3

DISCONNECT SWITCH BLOWER/MOTOR ACCESS DOOR

DIRECT FIRED CONDENSER MODULE

CONDENSER SUPPLEMENT MODULE

FILTER ACCESS DOOR

SLOPED FILTER INTAKE

WATER DRAIN WATER INLET (BELOW) **

AIRFLOW

General Construction: Profile plates shall be formed from G90 galvanized steel. Profile plates shall vary in size per unit design. Profile plates shall be mounted along the same plane as the discharge of the burner. Design shall incorporate properly torqued permanently mounted spring hinges.

Direct Fired (DF) Profile Plate Assembly

Application: Spring-loaded burner profile plates are engineered to automatically react to the momentum of a fresh air stream, without the need for any motors or actuators to mechanically adjust them. When this feature is utilized, the unit shall be designed for manual control. Ventilation (80%) requirement.

Labeling: The following labels shall be included in the DF unit's TL, listing and comply with combined surface temperature ANSI Z83.4 and CSA 37 (combustion-inducing DF heaters) and ANSI Z83.18 (re-circulating DF heaters).

Installation: Burners shall have patented US Patent Nos. US6425329A2, self-adjusting profile plates designed to ensure proper air velocity and pressure drop across the burner. Profile plates shall allow burners to achieve clean combustion by limiting by-product levels to a maximum of 50ppm of carbon monoxide (CO), and 50ppm of nitrogen dioxide (NO2).

R410A REFRIGERANT

Labeling: Burners shall have patented US Patent Nos. US6425329A2, self-adjusting profile plates designed to ensure proper air velocity and pressure drop across the burner. Profile plates shall allow burners to achieve clean combustion by limiting by-product levels to a maximum of 50ppm of carbon monoxide (CO), and 50ppm of nitrogen dioxide (NO2).

Installation: Burners shall have patented US Patent Nos. US6425329A2, self-adjusting profile plates designed to ensure proper air velocity and pressure drop across the burner. Profile plates shall allow burners to achieve clean combustion by limiting by-product levels to a maximum of 50ppm of carbon monoxide (CO), and 50ppm of nitrogen dioxide (NO2).

R410A REFRIGERANT

Labeling: Burners shall have patented US Patent Nos. US6425329A2, self-adjusting profile plates designed to ensure proper air velocity and pressure drop across the burner. Profile plates shall allow burners to achieve clean combustion by limiting by-product levels to a maximum of 50ppm of carbon monoxide (CO), and 50ppm of nitrogen dioxide (NO2).

Installation: Burners shall have patented US Patent Nos. US6425329A2, self-adjusting profile plates designed to ensure proper air velocity and pressure drop across the burner. Profile plates shall allow burners to achieve clean combustion by limiting by-product levels to a maximum of 50ppm of carbon monoxide (CO), and 50ppm of nitrogen dioxide (NO2).