MODULAR OUTDOOR SIDE DISCHARGE DIRECT FIRED RECIRCULATING HEATER WITH COOLING, EVAPORATIVE COOLER INTAKE AND INTAKE HOOD

IHECMBDFSAHCC-MPU-15
REV.#3 06/15/2015



ALL DIMENSIONS ARE NOMINAL AND GIVEN IN INCHES.

MODEL	UNIT DIMENSIONS A	B	C	D	E	F	G	H	CURB/RAIL J	K	L	LL	DISCHARGE OPENING N	P	R	S	RETURN DAMPER OPENING T	U	V	W	X	WATER INLET AA	AB	DRAIN OPENING AC	AD	FILTER SIZE & QTY	MAX. FILTER VELOCITY
D.500-G18	210-1/8	54-3/8	56-3/8	51-1/8	5-1/4	51-5/8	9-1/2	90-1/16	35	84	126-1/4	165-11/16	29-5/8	30	11-1/2	7-3/8	28	8	7	4-1/2	30	4-1/2	5-3/4	20	19	16"x20"x2" (6)	@8000 CFM = 762 FPM
D.750-G18	210-1/8	54-3/8	56-3/8	51-1/8	5-1/4	51-5/8	9-1/2	90-1/16	35	84	126-1/4	165-11/16	29-5/8	30	11-1/2	7-3/8	28	8	7	4-1/2	30	4-1/2	5-3/4	20	19	16"x20"x2" (6)	@8000 CFM = 762 FPM
D.1000-G18	210-1/8	54-3/8	56-3/8	51-1/8	5-1/4	51-5/8	9-1/2	90-1/16	35	84	126-1/4	165-11/16	29-5/8	30	11-1/2	7-3/8	28	8	7	4-1/2	30	4-1/2	5-3/4	20	19	16"x20"x2" (6)	@8000 CFM = 762 FPM
D.1000-920	262-1/2	60-7/16	64-3/8	59-1/8	5-1/4	76-3/8	13-9/16	120-5/8	42	115-3/16	169-1/2	217-1/2	36-3/4	34	12-1/2	7-3/8	33	10	11	8	36	4-1/2	5-3/4	23-1/2	17-1/2	16"x20"x2" (10)	@13000 CFM = 743 FPM
D.1500-920	262-1/2	60-7/16	64-3/8	59-1/8	5-1/4	76-3/8	13-9/16	120-5/8	42	115-3/16	169-1/2	217-1/2	36-3/4	34	12-1/2	7-3/8	33	10	11	8	36	4-1/2	5-3/4	23-1/2	17-1/2	16"x20"x2" (10)	@13000 CFM = 743 FPM

UNIT INFORMATION

MODEL	BURNER LENGTH	BTU RANGE (MBH) BTU LOW	BTU HIGH	GAS PRESSURE MIN	MAX	GAS CONNECTION "I" (NPT)	TONNAGE RANGE MIN	MAX
D.500-G18	12"	18	550	7" WC	14" WC	1	15 Ton	15 Ton
D.750-G18	18"	27.5	825	7" WC	14" WC	1	15 Ton	15 Ton
D.1000-G18	24"	36.6	1100	7" WC	14" WC	1	15 Ton	15 Ton
D.1000-920	24"	36.6	1100	7" WC	5 PSI	1-1/4	15 Ton	15 Ton
D.1500-920	30"	45.8	1375	7" WC	5 PSI	1-1/4	15 Ton	15 Ton

STANDARD EVAPORATIVE COOLING UNIT

TOT. WEIGHT	MEDIA SIZE & QTY	VEL. @ MAX. CFM	NOZZLES	MAX. FLOW RATE
1995 LBS	20"x25"x2" (8)	348 FPM	14	7 GPH
2000 LBS	20"x25"x2" (8)	348 FPM	14	7 GPH
2005 LBS	20"x25"x2" (8)	348 FPM	14	7 GPH
3220 LBS	16"x20"x2" (15)	572 FPM	24	12 GPH
3235 LBS	16"x20"x2" (15)	572 FPM	24	12 GPH

CELDEK EVAPORATIVE COOLING UNIT

TOT. WEIGHT	MEDIA SIZE & QTY	VEL. @ MAX. CFM	NOZZLES	MAX. FLOW RATE
1985 LBS	30"x36"x12"	1067 FPM	28	8.4 GPH
1990 LBS	30"x36"x12"	1067 FPM	28	8.4 GPH
1995 LBS	30"x36"x12"	1067 FPM	28	8.4 GPH
3190 LBS	38"x43"x12"	1322 FPM	35	10.15 GPH
3205 LBS	38"x43"x12"	1322 FPM	35	10.15 GPH

MAX. ROOF OPENING 2" SMALLER THAN CURB OUTSIDE DIMENSION

*ADD CONDENSING UNIT WEIGHT TO WEIGHT IN TABLE ABOVE

**MAX. EVAP WATER PRESSURE = 50 PSI @ 70 DEG. F

CONDENSER INFORMATION

MODEL	WEIGHT*	TONNAGE #1	#2	#3	CC	DD	EE
15 TON-G18	591 LBS	5 TON	5 TON	5 TON	32-13/16	76-3/16	70-7/8
15 TON-920	591 LBS	5 TON	5 TON	5 TON	32-13/16	97-3/16	91-15/16

R410A REFRIGERANT

OPTIONAL MIXING BOX FILTERS FILTER SIZE & QTY
15"x20"x2" (4), 15"x15"x2" (2)
15"x20"x2" (4), 15"x15"x2" (2)
15"x20"x2" (4), 15"x15"x2" (2)
18"x25"x2" (4), 16"x20"x2" (2)
18"x25"x2" (4), 16"x20"x2" (2)

Direct Fired Profile Plate Specifications:

Description:
Direct fired burners shall have patented (US Patent No.: US6629523B2), self-adjusting profile plates designed to ensure proper air velocity and pressure drop across the burner. Profile plates shall allow burners to achieve clean combustion by limiting by-product levels to a maximum of 5ppm of carbon monoxide (CO), and 0.5ppm of nitrogen dioxide (NO2).

Application:
Spring-loaded burner profile plates are engineered to automatically react to the momentum of a fresh air stream, without the need for any motors or actuators to mechanically adjust them. With this feature, all DF units are designed for demand control ventilation (DCV) requirements.

Certifications:
All profile plate assemblies shall be included in the DF unit's ETL listing and comply with combined safety standards ANSI Z83.4 and CSA 3.7 (non-recirculating DF heaters) and ANSI Z83.18 (recirculating DF heaters).

General Construction:
-Profile plates shall be formed from G90 galvanized steel.
-Profile plates shall vary in size per unit.
-Profile plates shall be mounted along the same plane as the discharge of the burner.
-Design shall incorporate properly torqued, permanently mounted spring hinges.
-Spring hinges shall be made from plated steel.



Direct Fired (DF) Profile Plate Assembly