MODULAR OUTDOOR SIDE DISCHARGE ELECTRIC HEATER PACKAGED UNIT WITH COOLING, LPD EVAPORATIVE COOLER INTAKE, V-BANK AND INTAKE HOOD

IHVBLPDECEHSAHCC-MPU-15
REV.#2 06/15/2015



ALL DIMENSIONS ARE NOMINAL AND GIVEN IN INCHES.

	UNIT DIMENSIONS						CURB/RAIL				DISCHARGE OPENING				WATER INLET		DRAIN OPENING		FILTER SIZE & QTY
MODEL	A	B	C	D	E	F	J	K	L	LL	N	P	R	S	AA	AB	AC	AD	
E3-G18	242-5/8	54-3/8	56-3/8	51-1/8	5-1/4	76-3/8	35	84	126-1/4	168-1/2	29-5/8	30	11-1/2	7-3/8	4-1/2	41-1/8	23-1/2	52-7/8	16"x20"x2" (15)
E4-920	297-7/8	60-7/16	64-3/8	59-1/8	5-1/4	71-3/8	42	115-3/16	169-1/2	223-13/16	36-3/4	34	12-1/2	7-3/8	4-1/2	41-1/8	28-7/8	52-7/8	20"x25"x2" (12)

UNIT INFORMATION.

MODEL	TONNAGE RANGE	
	MIN	MAX
E3-G18	15 Ton	15 Ton
E4-920	15 Ton	15 Ton

CELDEK EVAPORATIVE COOLING UNIT			
TOT. WEIGHT	MEDIA SIZE & QTY	NOZZLES	MAX. FLOW RATE
2145 LBS	38"x43"x12"	35	10.15 GPH
3125 LBS	45"x54"x12"	42	12.6 GPH

*ADD CONDENSING UNIT WEIGHT TO WEIGHT IN TABLE ABOVE ** MAX EVAP WATER PRESSURE = 50 PSI @ 70 DEG F

CONDENSER INFORMATION							
MODEL	WEIGHT*	TONNAGE			CC	DD	EE
		#1	#2	#3			
15 TON-G18	591 LBS	5 TON	5 TON	5 TON	32-13/16	76-3/16	70-7/8
15 TON-920	591 LBS	5 TON	5 TON	5 TON	32-13/16	97-3/16	91-15/16

R410A REFRIGERANT