MODULAR OUTDOOR DOWN DISCHARGE DIRECT FIRED RECIRCULATING HEATER–ROOF TOP PACKAGE WITH COOLING, LPD EVAPORATIVE COOLER INTAKE, V–BANK AND INTAKE HOOD

IHVBLPDECMBDFSAHCCDPRTP-MPU
REV.#3 06/15/2015



CONDENSER INFORMATION						
MODEL	WEIGHT*	TONNAGE #1	TONNAGE #2	CC	DD	EE
2 TON-G10	119 LBS	2 TON	N/A	26-5/16	56-1/16	52-3/8
3 TON-G10	134 LBS	3 TON	N/A	33-5/16	63-1/16	59-3/8
5 TON-G10	253 LBS	2 TON	3 TON	33-5/16	63-1/16	59-3/8
5 TON-G10	302 LBS	2.5 TON	2.5TON	32-13/16	62-9/16	58-7/8
5 TON-G15	197 LBS	5 TON	N/A	32-13/16	69-9/16	65-7/8
7.5 TON-G15	348 LBS	2.5 TON	5 TON	32-13/16	69-9/16	65-7/8
8 TON-G15	331 LBS	3 TON	5 TON	33-5/16	71-11/16	68
10 TON-G15	394 LBS	5 TON	5 TON	32-13/16	69-9/16	65-7/8
10 TON-G18	394 LBS	5 TON	5 TON	32-13/16	76-3/16	70-7/8
10 TON-920	394 LBS	5 TON	5 TON	32-13/16	97-3/16	91-15/16

R410A REFRIGERANT

ALL DIMENSIONS ARE NOMINAL AND GIVEN IN INCHE

UNIT DIMENSIONS									CURB/RAIL					DISCHARGE OPENING				RETURN DAMPER OPENING					WATER INLET		DRAIN OPENING	
MODEL	A	B	C	D	E	F	G	H	J	K	L	M	MM	N	P	R	S	T	U	V	W	X	AA	AB	AC	AD
D.250-G10	241-3/4	39-3/8	42-3/4	39	3-3/4	53-5/8	7-13/16	95-7/16	21	71	106	166-5/8	198-1/16	3-9/16	13-7/8	36-13/16	11-1/2	14	8	14	12-1/2	18	4-1/2	38-1/2	18	48-1/4
D.500-G10	241-3/4	39-3/8	42-3/4	39	3-3/4	53-5/8	7-13/16	95-7/16	21	71	106	166-5/8	198-1/16	3-9/16	13-7/8	36-13/16	11-1/2	14	8	14	12-1/2	18	4-1/2	38-1/2	18	48-1/4
D.250-G15	267-3/4	49-3/8	47-3/4	44	3-3/4	51-5/8	7-13/16	109-7/16	31	79	124	190-5/8	227-1/16	4-5/16	22-3/8	46-9/16	18	22-3/4	8	11	7-1/2	24	4-1/2	44	20	57-1/4
D.500-G15	267-3/4	49-3/8	47-3/4	44	3-3/4	51-5/8	7-13/16	109-7/16	31	79	124	190-5/8	227-1/16	4-5/16	22-3/8	46-9/16	18	22-3/4	8	11	7-1/2	24	4-1/2	44	20	57-1/4
D.750-G15	267-3/4	49-3/8	47-3/4	44	3-3/4	51-5/8	7-13/16	109-7/16	31	79	124	190-5/8	227-1/16	4-5/16	22-3/8	46-9/16	18	22-3/4	8	11	7-1/2	24	4-1/2	44	20	57-1/4
D.500-G18	267	54-3/8	56-3/8	51-1/8	5-1/4	76-3/8	9-1/2	114-7/16	35	84	133	199-5/8	239-1/16	6-5/16	22-3/8	49-1/2	18	28	8	7	4-1/2	30	4-1/2	41-1/8	23-1/2	52-7/8
D.750-G18	267	54-3/8	56-3/8	51-1/8	5-1/4	76-3/8	9-1/2	114-7/16	35	84	133	199-5/8	239-1/16	6-5/16	22-3/8	49-1/2	18	28	8	7	4-1/2	30	4-1/2	41-1/8	23-1/2	52-7/8
D.1000-G18	267	54-3/8	56-3/8	51-1/8	5-1/4	76-3/8	9-1/2	114-7/16	35	84	133	199-5/8	239-1/16	6-5/16	22-3/8	49-1/2	18	28	8	7	4-1/2	30	4-1/2	41-1/8	23-1/2	52-7/8
D.1000-920	328-1/4	60-7/16	64-3/8	59-1/8	5-1/4	71-3/8	13-9/16	151	42	115-3/16	171-3/16	255-7/8	303-7/8	5-1/4	31-1/2	56-13/16	23-1/2	33	10	11	8	36	4-1/2	41-1/8	28-7/8	52-7/8
D.1500-920	328-1/4	60-7/16	64-3/8	59-1/8	5-1/4	71-3/8	13-9/16	151	42	115-3/16	171-3/16	255-7/8	303-7/8	5-1/4	31-1/2	56-13/16	23-1/2	33	10	11	8	36	4-1/2	41-1/8	28-7/8	52-7/8

OPTIONAL MIXING BOX FILTERS
FILTER SIZE & QTY
10"x16"x2" (5)
10"x16"x2" (5)
20"x25"x2" (2), 16"x25"x2" (1)
20"x25"x2" (2), 16"x25"x2" (1)
20"x25"x2" (2), 16"x25"x2" (1)
15"x20"x2" (4), 15"x15"x2" (2)
15"x20"x2" (4), 15"x15"x2" (2)
15"x20"x2" (4), 15"x15"x2" (2)
18"x25"x2" (4), 16"x20"x2" (2)
18"x25"x2" (4), 16"x20"x2" (2)

EXHAUST UNIT DIMENSIONS			
MODEL #	Y	Z	ZZ ***
DU12HFA	14-1/2	22	19
NCA8FA DU25HFA DU30HFA DU33HFA	18-1/2	27-1/4	21
NCA10FA DU50HFA	21-1/2	30-1/4	21
NCA14FA DU75HFA DU85HFA	23	33-3/4	24-3/4
NCA16FA	23-1/2	39-3/8	28
NCA18FA	29-1/2	38-7/8	28
NCA24FA	30-5/8	43-3/8	33
NCA30FA	33-1/2	52-3/4	40

UNIT INFORMATION

MODEL	BURNER LENGTH	BTU RANGE (MBH) BTU LOW	BTU RANGE (MBH) BTU HIGH	GAS PRESSURE MIN	GAS PRESSURE MAX	GAS CONNECTION "I" (NPT)	TONNAGE RANGE MIN	TONNAGE RANGE MAX	FILTERS FILTER SIZE & QTY
D.250-G10	6'	18	275	7" WC	14" WC	3/4	2 Ton	5 Ton	16"x20"x2" (8)
D.500-G10	12"	18	550	7" WC	14" WC	3/4	2 Ton	5 Ton	16"x20"x2" (8)
D.250-G15	6'	18	275	7" WC	14" WC	1	2 Ton	5 Ton	20"x25"x2" (8)
D.500-G15	12"	18	550	7" WC	14" WC	1	5 Ton	10 Ton	20"x25"x2" (8)
D.750-G15	18"	27.5	825	7" WC	14" WC	1	5 Ton	10 Ton	20"x25"x2" (8)
D.500-G18	12"	18	550	7" WC	14" WC	1	5 Ton	10 Ton	16"x20"x2" (15)
D.750-G18	18"	27.5	825	7" WC	14" WC	1	5 Ton	10 Ton	16"x20"x2" (15)
D.1000-G18	24"	36.6	1100	7" WC	14" WC	1	10 Ton	10 Ton	16"x20"x2" (15)
D.1000-920	24"	36.6	1100	7" WC	5 PSI	1-1/4	10 Ton	10 Ton	20"x25"x2" (12)
D.1500-920	30"	45.8	1375	7" WC	5 PSI	1-1/4	10 Ton	10 Ton	20"x25"x2" (12)

CELDEK EVAPORATIVE COOLING UNIT			
TOT. WEIGHT	MEDIA SIZE & QTY	NOZZLES	MAX. FLOW RATE
1515 LBS	25"x32"x12"	20	6.5 GPH
1520 LBS	25"x32"x12"	20	6.5 GPH
2020 LBS	30"x36"x12"	28	8.4 GPH
2025 LBS	30"x36"x12"	28	8.4 GPH
2030 LBS	30"x36"x12"	28	8.4 GPH
2550 LBS	38"x43"x12"	35	10.15 GPH
2555 LBS	38"x43"x12"	35	10.15 GPH
2560 LBS	38"x43"x12"	35	10.15 GPH
3755 LBS	45"x54"x12"	42	12.6 GPH
3770 LBS	45"x54"x12"	42	12.6 GPH

*ADD CONDENSING UNIT WEIGHT TO WEIGHT IN TABLE ABOVE
**MAX. EVAP WATER PRESSURE = 50 PSI @ 70 DEG. F

Direct Fired Profile Plate Specifications:

Description:
Direct fired burners shall have patented (US Patent No: US6629523B2), self-adjusting profile plates designed to ensure proper air velocity and pressure drop across the burner. Profile plates shall allow burners to achieve clean combustion by limiting by-product levels to a maximum of 5ppm of carbon monoxide (CO), and 0.5ppm of nitrogen dioxide (NO2).

Application:
Spring-loaded burner profile plates are engineered to automatically react to the momentum of a fresh air stream, without the need for any motors or actuators to mechanically adjust them. With this feature, all DF units are designed for demand control ventilation (DCV) requirements.

Certifications:
All profile plate assemblies shall be included in the DF unit's ETL listing and comply with combined safety standards ANSI Z83.4 and CSA 3.7 (non-recirculating DF heaters) and ANSI Z83.18 (recirculating DF heaters).

General Construction:
-Profile plates shall be formed from G90 galvanized steel.
-Profile plates shall vary in size per unit.
-Profile plates shall be mounted along the same plane as the discharge of the burner.
-Design shall incorporate properly torqued, permanently mounted spring hinges.



Direct Fired (DF) Profile Plate Assembly