

R1-E.504-G10

CFM	Static Pressure in Inches W.G.								
	0.000	0.250	0.500	0.750	1.000	1.250	1.500	1.750	2.000
	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP	RPM/BHP
1200	365 / 0.07	568 / 0.15	740 / 0.24	886 / 0.38	1014 / 0.54				
1600	487 / 0.18	643 / 0.27	789 / 0.37	920 / 0.50	1038 / 0.65	1146 / 0.83	1247 / 1.04	1341 / 1.25	1430 / 1.48
2000	608 / 0.34	733 / 0.46	856 / 0.58	972 / 0.71	1079 / 0.85	1180 / 1.03	1275 / 1.22	1363 / 1.44	1448 / 1.68
2400	730 / 0.60	833 / 0.73	938 / 0.88	1039 / 1.02	1136 / 1.17	1228 / 1.34	1316 / 1.52	1399 / 1.73	1480 / 1.96
2800	851 / 0.95	940 / 1.11	1029 / 1.27	1119 / 1.44	1206 / 1.60	1289 / 1.78	1370 / 1.96		
3200	972 / 1.41	1050 / 1.60	1127 / 1.78	1208 / 1.97					

Max Sizeable RPM = 1600 RPM. Table shown extended beyond this point for reference only.